

MITSUBISHI

MITSUBISHI TRACTOR

GX5000



**Simple,
Powerful &
Tough.**

MITSUBISHI TRACTOR GX5000

Specifications

| MODEL | GX5000 |
|--------------------------------------|--|
| Engine | |
| Type | Water Cooled 4-Cycle, 4-Cylinder Diesel |
| Engine Model | Mitsubishi S4Q2 |
| Engine Output (HP) | 50 |
| Rated RPM (RPM) | 2800 |
| Number of Cylinder | 4 |
| Displacement (L) | 2.505 |
| Battery (V/Ah) | 12/64 |
| Fuel Tank capacity (L) | 40 |
| Dimensions | |
| Front Tyre (AG) | (8-18) |
| Rear Tyre (AG) | (12.4-28) |
| Tread Front | 1220 |
| Tread Rear | 1150/1255/1345/1440/ 1545/1645 |
| Wheelbase | 1970 |
| Overall Length | 3500 |
| Overall Width | 1500 |
| Height | 1600 |
| Ground Clearance | 365 |
| Turning Radius | 2.8 |
| Weights | 1700 |
| PowerTrain | |
| Clutch | Dry, Single |
| Transmission Type | Synchro |
| Speed Steps | F16-R16 |
| Shuttle Transmission | STD |
| Brake Type | Wet Disk |
| Parking Brake | Latch Type |
| Rear PTO | STD |
| PTO RPM | 579/881/1098 |
| PTO Shaft | SAE 1-3/8, 6-Sprine |
| IND PTO | NA |
| Mid PTO | NA |
| Hitch | |
| Category | Cat.1 |
| Lift Capacity at Hitch Ball (kgf) | 1900 |
| Position Control | STD |
| Draft Control | OPT |
| Draw Bar | OPT(Swing) |
| Hydraulics | |
| Pump Capacity Main (liter/min) | 24.2 |
| P/S | 23.5 |
| Hydraulic Outlet Block | STD1 |
| Auxiliary Valve | NA |
| Max. Pressure (kgf/cm ²) | 170 |
| Oil Filter Type | Cartridge Type |
| Notes | |
| ROPS | NA |
| Tyre | Thailand Supply |



Powerful 4 cylinder water cooled diesel engine gives dynamic power and stable torque with low noise and minimum vibration.

 MITSUBISHI AGRICULTURAL MACHINERY CO., LTD.

Gotanda Nomura Shoken Bldg.6th Floor
1-5-1, Nishigotanda, Shinagawa-ku, Tokyo
141-0031 Japan
Phone: +81-3-5759-8245 Fax: +81-3-5759-8246
<http://www.mam.co.jp>

Specifications subject to change without notice.

