



MITSUBISHI TRACTOR



MT28/MT36

Sensitivity that has been continuously built.

NEW

Mitsubishi Compact Tractor
cover all aspects of Ground and Lawn care

F&R Synchro Shuttle Lever



One Touch Independent PTO Clutch



High Lift Capacity of 3P-link



Specifications

| MODEL | | MT28 | MT28H | MT36 | MT36H |
|------------------------------------|---|------------------------------|--------------|------------------------|--------------|
| Engine | Model | S3L2 | | S3L3L | |
| | Type | 4 cycle, Water-Cooled Diesel | | | |
| | Max.output PS(kW)/rpm | 28(20.6)/2600 | | 36.2(27.0)/2600 | |
| | PTO HP | 20 | 19.5 | 28 | 27.5 |
| | No. of Cylinders | 3 | | 3 | |
| | Displacement (cc) | 1318 | | 1662 | |
| Fuel System | Fuel Capacity (litter) | 24.5 | | | |
| | Injection Type | I.D.I | | | |
| | Engine Start | key | | | |
| Drivetrain | Transmission Type | Gear | HST | Gear | HST |
| | Speeds | 8F-8R | 3Range | 8F-8R | 3Range |
| | Shuttle (F&R) | synchro | N/A | synchro | N/A |
| | Brakes | Wet Disc | | | |
| Hydraulics | Position Control | Standard | | | |
| | Main Pump Capacity (L/min) | 29.6 | | 29 | |
| | Steering Pump Capacity (L/min) | 12.7 | | 12.7 | |
| | Draft Control | Option | | | |
| | Auxiliary Valve | Option | | | |
| PTO | Type | Independent | Live | Independent | Live |
| | Rear PTO RPM (rpm) | 540/1000 | 540 | 540/1000 | 540 |
| | Mid PTO | N/A | Option(2000) | N/A | Option(2000) |
| Steering | Power Steering | Hydrostatic(Standard) | | | |
| | Min Turning Radius (m) (W/AG Tyre Brake) | 2.4 | | | |
| Hitch | Type | Category I | | | |
| | Lift Capacity at Hitch ball (kgf) | 1200 | | | |
| Tyres | AG Tyre Front | 7-16 | 7-16 | 7-16 | 7-16 |
| | Rear | 11.2-24 | 11.2-24 | 12.4-24 | 12.4-24 |
| | Turf Tyre Front | 25×8.50-14 | 25×8.50-14 | 212/80D15 | 212/80D15 |
| | Rear | 13.6-16 | 13.6-16 | 355/80D20 | 355/80D20 |
| Dimensions (W/AG Tyres) | | at 7-16/11.2-24 | | at 7-16/12.4-24 | |
| | Wheelbase (mm) | 1710 | | 1750 | |
| | Overall Width (mm) | 1400 | | 1400 | |
| | Overall Length (mm) | 3190 | | 3190 | |
| | Hight (Top of Rear ROPS) (mm) | 2385 | | 2410 | |
| | (Top of Front ROPS) (mm) | 2225 | | 2235 | |
| | Ground Clearance (mm) | 330 | | | |
| | Weight (Rear ROPS) (kg) | 1170 | 1175 | 1205 | 1210 |
| | (Front ROPS) (kg) | 1190 | 1195 | 1225 | 1230 |

Specifications subject to change without notice.



Gotanda Nomura Shoken Bldg. 6th Floor
1-5-1, Nishigotanda, Shinagawa-ku,
Tokyo 141-0031 Japan
<http://www.mam.co.jp>