

## Principal specification : Mitsubishi Mini cultivator MFR30A

Name		POPLI	
Model name		MFR30A	
Type		—	H
Dimension	Overall length (mm)	1370[725]	1370[780] * <sup>1</sup>
	Overall width (mm)	550	
	Overall height (mm)	1090[635]	
Weight (kg)		54	57 * <sup>1</sup>
Engine	Model	Mitsubishi GB101	
	Type	4Cycle OHV Air-cooled gasoline engine	
	Displacement (L)	0.098	
	Rated output (kW{PS}/rpm)	1.5{2.0}/3300	
	Max. output (kW{PS})	2.2{3.0}	
	Fuel	Unleaded gasoline	
	Fuel tank capacity (L)	1.2	
Starting method		Recoil (Miracle Start * <sup>2</sup> )	
Main clutch		V-belt tension type (deadman lever)	
Steering System		Differential gear without lock device	
Wheel (Diameter xwidth) (mm)		φ350x55 (Cultivation Tire)	
Wheel track (mm)		405	
Speed steps		F1•R1 (Cultivation 1)	
Travel speed (m/s)	forward	0.23	
	reverse	0.17	
Tread adjustment		4 steps (Travel 1• Cultivation 3)	
Rotary	Type	Center drive type	
	Tilling width (mm)	500	
	Shape of tine	(Outside) Hatch tine / (Inside) Hatch tine (16pieces)	
	Shaft speed (rpm)	141	
	Rotary speed step	1 (Uniaxial forward/reverse-rotating rotary shaft) * Plow on the spot range	

There are some possibilities to change this specification without prior notice for improvement

\*<sup>1</sup>The condition that hitch is mounted on the machine

\*<sup>2</sup>「Miracle Start」 is registered trade marks of Mitsubishi Heavy Industries Co., Ltd.