Principal specification: Mitsubishi Mini cultivator MMR300A

Model name			MMR300A
Dimension	Overall l	ength (mm)	1355[1130]
	Overall v	vidth (mm)	575
	Overall height (mm)		1090[600]
Weight (kg)			61
Engine	Model		GB101PN
	Туре		4Cycle OHV Air-cooled gasoline engine
	Displacement (L)		0.098
	Rated output (kW{PS}/rpm)		1.5{2.0}/3300
	Max. output (kW{PS})		2.2{3.0}
	Fuel		Unleaded gasoline
	Fuel tank capacity (L)		1.2
	Starting method		Recoil (Miracle Start <sup>*</sup> )
Tire size			100/85D6
Main clutch			V-belt tension type
Steering system			Differential gear with lock device
Speed steps			F2•R1
Traval speed	1 (m /s)	forward	0.22/0.93
Travel speed (m/s)		reverse	0.16
Rotary	Туре		Center drive type
	Rotary shifting step		1
	Rotating speed (rpm)		141
	Tilling width (mm)		500
	Shape of tine		Outside:hatch tine/Inside: hatch tine
	Rotary type		Uniaxial forward/reverse-rotating rotary shaft

There are some possibilities to change this specification without prior notice for improvement

 $<sup>*{\</sup>sl f}{\sl Miracle Start}{\sl j} is registered trade marks of Mitsubishi Heavy Industries Co., Ltd.$