

Principal specification : Mitsubishi Mini cultivator MMR400A*600A

Model name		MMR400AUN	MMR600A	MMR600AL	MMR600AR	MMR600AUN	
Dimension	Overall length (mm)	1340[1380]		1385[1375]	1340[1380]		
	Overall width (mm)	600[600]					
	Overall height (mm)	1130[715]		1105[730]	1130[715]		
Weight (kg)		86		88	89	87	
Engine	Model	GB1311LN	GB181LN				
	Type	4Cycle OHV Air-cooled gasoline engine					
	Displacement (L)	0.126	0.181				
	Rated output (kW{PS}/rpm)	1.7{2.3}/1500	2.6{3.5}/1500				
	Max. output (kW{PS})	3.0{4.2}	4.6{6.3}				
	Fuel	Unleaded gasoline					
	Fuel tank capacity (L)	2.0					
Starting method		Recoil (Miracle Start [®])					
Tire size		3.50-7		4.00-7	3.50-7		
Wheel track (mm)		200•228•280•390		390	200•228•280•390		
Main clutch		V-belt tension type					
Steering system		Differential gear with lock device					
Speed steps		F2×R1					
Travel speed (m/s)	forward	0.28、1.01		0.32、1.16	0.28、1.01		
	reverse	0.34		0.38	0.34		
Handle		Loop handle					
Rotary	Type	Center drive type					
	Rotary shifting step	(Standard 1) (Counter 1)					
	Rotating speed (rpm)	(standard)248 (counter)350	(standard)204 (counter)221		(standard)248 (counter)350		
	Tilling width (mm)	(standard)264•550 (counter)314•540	550			(standard)264•550 (counter)314•540	
	Tine	Hatched tine / Soil-life tine	Forward-Reverse tine			Hatched tine / Soil-life tine	
	Rotary cover	Openable	Fixed type			Openable	
	Rotary type	Forward/Reverse-rotating			W-type Forward/ Reverse-rotating	Forward/ Reverse-rotating	
Tail wheel		Moving tail wheel					
Adjust handle height / handle storage		One-touch lever 4steps and storage					

There are some possibilities to change this specification without prior notice for improvement

*「Miracle Start」 is registered trade marks of Mitsubishi Heavy Industries Co., Ltd.