

## Principal specification : Mitsubishi cultivator MMR78A・MMR88B

Model name		MMR78A	MMR78AUN	MMR78AUND	MMR88B	MMR88BR
Dimension	Overall length (mm)	1550	1510	1580	1635	1620
	Overall width (mm)	700	650		700	
	Overall height (mm)	1125	1145	1100	1090	1100
Weight (kg)		121	118	130	137	139
Engine	Model	GB181L			GB221L	
	Type	4Cycle OHV Air-cooled gasoline engine				
	Displacement (L)	0.181			0.215	
	Rated output (kW{PS}/rpm)	2.9{4.0}/1700			3.7{5.1}/1800	
	Max. output (kW{PS})	4.6{6.3}			5.1{7.0}	
	Fuel	Unleaded gasoline				
	Fuel tank capacity (L)	2.8				
Starting method		Recoil (Miracle Start <sup>®</sup> )				
Main clutch		V-belt tension type				
Steering system		Ball clutch				
Tire size		4.00-7	3.50-7	4.00-8	4.00-9	4.00-8
Wheel track (mm)		443~627	250~450	443~627	443~627	
Travel speed (m/s)	forward	0.19~1.07	0.25~1.15	0.32~1.45	0.22~1.22	0.21~1.16
	reverse	0.22~0.35	0.29~0.37	0.36~0.47	0.25~0.40	0.24~0.38
Speed steps		forward 2steps × reverse 1step				
Speed steps		2steps				
Shape of axle / Dimension (mm)		Hexagonal shape Diagonal dimension 26				
Rotary	Rotary type	Forward / Reverse-rotating rotary			V Center Rotary	Forward / Reverse-rotating V center rotary
	Tilling width (mm)	600	340・600	600	600	
	Rotating speed (rpm)	(standard)199 (counter)239	(standard)266 (counter)349	(standard)199 (counter)239	(slow speed) 221 (high speeds) 317	

There are some possibilities to change this specification without prior notice for improvement

\*「Miracle Start」 is registered trade marks of Mitsubishi Heavy Industries Co., Ltd.