

Principal specification : Mitsubishi Mini cultivator MM300E・MM300A

Model name		MM300E			MM300A				
Type		N	NU	ND	B	BU	RB	RBU	BD
Dimension	Overall length (mm)	1100			1110				
	Overall width (mm)	600			660				
	Overall height (mm)	1080		1045	1065			1030	
Weight (kg)		38	40	39	41	42		43	41
Engine	Model	GB101PN							
	Type	4Cycle OHV Air-cooled gasoline engine							
	Displacement (L)	0.098 {98}							
	Rated output (kW{PS}/rpm)	1.6 {2.2} / 3600 《2.2 {3.0}》							
	Fuel tank capacity (L)	1.2							
	Starting method	Recoil (Miracle Start [*])							
Main clutch		V-belt tension type (Deadman)		V-belt tension type (Retrnetype)	V-belt tension type (Deadman)			V-belt tension type (Retrnetype)	
Speed steps		F1			F2	F2/R1		F2	
Rotating speed (rpm)	forward	106			62・106				
	reverse	—			20		—		
Shape of axle / Dimension (mm)		φ20							
Tilling width (mm)		540			320/600				

There are some possibilities to change this specification without prior notice for improvement

*「Miracle Start」 is registered trade marks of Mitsubishi Heavy Industries Co., Ltd.