

Principal specification : Mitsubishi cultivator MM458BS・MM558BS・MM658AS・MM708AS

Model name		MM458BS	MM558AS	MM658AS	MM708AS
Dimension	Overall length (mm)	1530	1560		
	Overall width (mm)	660	700		
	Overall height (mm)	1080	1075	1110	
Weight (kg)		65	75	78	80
Engine	Model	GB131L	GB181L		GB221L
	Type	4Cycle OHV Air-cooled gasoline engine			
	Displacement (L)	0.126	0.181		0.215
	Rated output (kW{PS}/rpm)	2.3{3.1}/1800	3.0{4.2}/1700	3.4{4.7}/1800	3.7{5.0}/1800
	Max. output (kW{PS})	3.0{4.2}	4.2{5.7}	4.6{6.3}	5.1{7.0}
	Fuel	Unleaded gasoline			
	Fuel tank capacity (L)	2.8			
Starting method		Recoil (Miracle Start [®])			
Tire size		V-belt tension type			
Main clutch		Ball clutch			
Steering system		—			Built-in extension type
Tire size		100/85D6		4.00-7	
Wheel track (mm)		180~370(3steps)		200~490(8steps)	210~500(8steps)
Speed steps		forward 6steps・reverse 2steps			forward 4steps reverse 2steps
Main change steps		forward 3steps・reverse 1step			forward 2steps reverse 1step
Sub change steps		2			
Travel speed (m/s)	forward	0.19~1.79	0.13~1.44	0.16~1.77	0.15~1.56
	reverse	0.2、0.33	0.18、0.30	0.22、0.38	0.18、0.37
Shape of axle / dimension (mm)		Hexagonal shape Diagonal dimension 23			Hexagonal shape Diagonal dimension 26
Shape of wheel tube / dimension (mm)		Hexagonal shape Diagonal dimension 32			Hexagonal shape Diagonal dimension 35.3
PTO speed (rpm)		776、1271	732	745	

There are some possibilities to change this specification without prior notice for improvement

*「Miracle Start」 is registered trade marks of Mitsubishi Heavy Industries Co., Ltd.