

Principal specification : Mitsubishi cultivator MM758A・MM858A・MM1058A

Model name		MM758A	MM858A	MM1058A
Type		S	S	S
Dimension	Overall length (mm)	1630		
	Overall width (mm)	700		
	Overall height (mm)	1130	1150	1160
Weight (kg)		101	105	106
Engine	Model	GB290L		GB300L
	Type	4Cycle OHV Air-cooled gasoline engine		
	Displacement (L)	0.296		
	Rated output (kW{PS}/rpm)	3.7{5.0}/1500	4.4{6.0}/1800	5.5{7.5}/1800
	Max. output (kW{PS})	5.5{7.5}	5.8{8.0}	7.3{10.0}
	Fuel	Unleaded gasoline		
	Fuel tank capacity (L)	4.0		
Starting method		Recoil (Miracle Start [*])		
Main clutch		V-belt tension type		
Steering system		Ball Clutch		
Tire size		4.00-7	4.00-8	4.00-9
Wheel track (mm)		190~600 (12steps)		270~660 (11steps)
Travel speed	forward	0.52~5.23	0.61~6.13	0.64~6.41
		0.14~1.45	0.17~1.70	0.18~1.78
	reverse	0.72~1.18	0.84~1.38	0.88~1.44
		0.20~0.33	0.23~0.38	0.24~0.40
Main clutch steps		forward 3、reverse 1		
Sub clutch steps		2		
Shape of axle / dimension (mm)		Hexagonal shape Diagonal dimension 26		
Shape of wheel tubes / dimension (mm)		Hexagonal shape Diagonal dimension 35.3×26.3		
PTO speed (rpm)		654	698	
Shape of PTO shaft		Spline (φ19.8)		

There are some possibilities to change this specification without prior notice for improvement

*「Miracle Start」 is registered trade marks of Mitsubishi Heavy Industries Co., Ltd.