

## Principal specification : Mitsubishi Tractor GJ240

Model Name		GJ240		
Type		J	LJ	
Driving system		4WD		
Size	Overall length (mm)	3030		
	Overall width (mm)	1310	1325	
	Overall height (mm)	1935	1960	
	Minimum ground clearance (mm)	325	345	
	Weight (kg)	1035	1045	
Engine	Model Name	N843-D-1601		
	Type	Water cooled, 4 Cycle, 3 Cylinders Diesel Engine		
	Total displacement (L)	1.496		
	Output / Speed (kW{PS} /rpm)	17.7{24} /2600		
	Type of fuel	Diesel oil		
	Fuel tank capacity (L)	27		
Battery (V·Ah)		55B24R 12·36		
Driving unit	Tire	Front	6-14-4PR	7-14-4PR
		Rear	9.5-22-4PR	9.5-24-4PR
	Tread (mm)		1650	
	Tread (mm)	Front tire	1100	
		Rear tire	1010 · 1165	1050 · 1125
	Clutch type		Dry and Single plate type	
	Brake system		Disc type (Wet)	
	Steering system		Power steering (Hydraulic system)	
	Transmission type		Synchronesh type + Constant mesh type + Selective slide type	
	No. of Speeds		Forward 12 · Reverse 12	
	Driving speed (km/h) (Max.)	Forward	0.19~12.4 (13.6)	0.20~13.1 (14.3)
Reverse		0.19~11.0 (12.0)	0.20~11.6 (12.7)	
Minimum turning radius (m)		2.2		
PTO	PTO speed (rpm)	591 · 845 · 1362 · 991 (Reverse)		
	Shaft diameter (mm)	JIS 35		
Implement up/down system	Hydraulic control	Position control		
	Fitting method	3P linkage JIS class 1		
Safety frame		Mitsubishi 2F J30		
Safety Judgement Standard approved number		34111		
Required driver's license		License for Small-sized special motor vehicles		

## Principal Specification of Rotary

Model Name	RJ140SB/RJV140SB	RJ150SB/RJV150SB	RJ160SB/RJV160SB	RJ170SB/RJV170SB
Driving system	Side drive			
Fitting method	Special 3P linkage type			
Tilling width (mm)	1400	1500	1600	1700
No. of blade (pcs), Blade type	36 · LL type blade			
Weed-twinning preventive bar (pc)	1			