

Principal specification : Mitsubishi Tractor GS182 • GS202

Model Name		GS182		GS202				
Type		J	M	J	M	MT	SJ	
Driving system		4WD						
Size	Overall length (mm) (Tip of lower linkage)		2650					
	Overall width (mm)		1095			1145		
	Overall height (mm)		1900			1815		
	Tread (mm)		1380					
	Tread (mm)		Front tire	865			875	
			Rear tire	810 • 960			940	
Minimum ground clearance (mm)		335			265			
Weight (kg)		850			890		835	
Engine	Model Name		S3L					
	Type		Water cooled, 4 Cycle, 3 Cylinders Diesel Engine					
	Total displacement (L)		1.125					
	Output / Speed (kW {PS} /rpm)		13.2 {18} /2500		14.7 {20} /2500			
	Type of fuel		Diesel oil					
	Fuel tank capacity (L)		23					
	Battery (V•Ah)		55B24R 12•36					
Driving unit	Tire		Front	6.00-12-4PR			5.00-12-4PR	
			Rear	8.3-22-4PR			8-16-4PR	
	Clutch type		Dry and Single plate type					
	Brake system		Disc type (Wet)					
	Steering system		Power steering (Hydraulic system)					
	Transmission type		Constant mesh type + Selective sliding gear type ["MT" type: (HST)]					
	No. of Speeds		Forward 12 Reverse 12		Forward 30 Reverse 15		Forward 12 Reverse 12	
	Driving speed (km/h) (Max.)		Forward	0.24~13.10 (14.10)		0~12.37 (13.31)		0.19~13.01 (14.00)
			Reverse	0.22~12.04 (12.96)		0~8.19 (8.81)		0.17~11.96 (12.86)
	Minimum turning radius (m)		1.9					
PTO	PTO Speed (rpm)		Forward 566 • 816 • 1310 Reverse 952					
	Shaft diameter		JIS 35					
Implement up/down system	Control system		Position control					
	Fitting method		3P linkage JIS class 0					