

Principal specification : Mitsubishi Rice Transplanter LE50・LE60

Model name		LE50			LE60			
Type		UY	PUY	RUJ	—	UY	PUY	RUJ
Driving system		4WD						
Size	Overall length (mm)	3330						
	Overall width (mm)	1870			2100			
	Overall height (mm)	1910						
Weight (kg)		664	703	749	701	708	747	793
Min. ground clearance (mm) (Bottom of pitman arm)		430						
Engine	Model name	EH64						
	Type	Air cooled, V type, 2 cylinders, 4 Cycle, OHV Gasoline engine						
	Total displacement (L) {cc}	0.635{635}						
	Output (kw{PS})	11.8{16.0} (Max. 13.2{18.0})						
	Fuel tank capacity (L)	18						
	Starting method	Starter motor typeStarter (cell) motor						
Traveling unit	Steering system		Power steering					
	Front tire	Type	Wide rim		Rubber lug	Wide rim		
		Wheel dia. × Width (mm)	φ650×80					
	Rear tire	Type	rubber lug tire					
		Wheel dia. × Width (mm)	φ900×160		φ900×150	φ900×160		
	Tread	Front tire (mm)	940		1200 (W type 1320)			
		Rear tire (mm)	900		1200 (W type 1320)			
	Planting unit	Number of speeds (step)		HST Stepless speed change (Sub change shift : 2 steps)				
Planting method		Rotary type						
Number of planting rows (rows)		5		6				
Distance between rows (cm)		30		30 (33 for W spec.)				
Space between hills (cm)		19・22・26・30 (B spec. : 11・13・15・17・19・22)						
Number of stubs (stub/3.3m²)		60・50・42・37 (B spec. : 100・85・75・65・60・50)						
Planting depth (cm)		2～5 (5 options)						
Adjustable quantity per stub		20・26 (2 options) ※26 times at shipment						
Seedling condition	Seedling type	Mat type						
	Leaf stage ・ Plant height	2.0～3.5 leaves ・ 8～25cm						
Planting speed (m/s) [Slip ratio 5%]		0～1.60 (0～1.52)/Space bet. hills 26・30cm 0～1.30 (0～1.24)						
Planting efficiency (min./10a)		13～			11～			

○Seedling tray for 3 mats (one side) 7kg ○Seedling slider (one side) 24kg ○ seedling tray for 12 mats 58kg

※Some of the sub seedling trays, seedling sliders, and Back mirrors are sold separately.

There are some possibilities to change this specification without prior notice for improvement