

Principal specification : Mitsubishi Rice Transplanter LE80D

Model Name		LE80D		
Type		F	PF	RF
Driving system		4WD		
Size	Overall length (mm) (At working)	3375 (3390)		
	Overall width (mm) (At working)	2220 (2780)		
	Overall height (mm) (At working)	1595 (1580)		
Weight (kg) (Including oil & lubricants)		908	963	1031
Min. ground clearance (mm) (Bottom of pitman arm)		460		
Engine	Model Name	E673L-D		
	Type	Water cooled, 3 Cylinders, 4 cycle Diesel Engine		
	Total displacement (L) {cc}	0.761{761}		
	Output (kW{PS})	15.1{20.5}		
	Fuel tank capacity (L)	22		
	Starting method	Starter (cell) motor		
Traveling unit	Steering system		Power steering	
	Front tire	Type	Blowout-free & Wide type	
		Wheel dia. × Width (mm)	φ650×95	
	Rear tire	Type	Large rim rubber lug tire	
		Wheel dia. × Width (mm)	φ950×150	
	Tread	Front tire (mm)	1200	
		Rear tire (mm)	1200	
Number of speeds (step)		HST Stepless speed change (Sub change shift : 2 steps)		
Planting unit	Planting method		Rotary type	
	Number of planting rows (rows)		8	
	Distance between rows (cm)		30 (W type 33)	
	Space between hills (cm)		19•22•26•30 (B type : 11•13•15•17•19•22)	
	Number of stubs (stub/3.3m ²)		60•50•42•37 (B type : 100•85•75•65•60•50)	
	Planting depth (cm)		2 to 5 (5 options)	
	Adjustable quantity per stub		No. of lateral feed time : 20/26 (2 options) ※26 times at shipping from factory	
Seedling condition	Seedling type		Mat type	
	Leaf stage • Plant height		2.0-4.5 leaves, 8-25cm	
Planting speed (m/s) (Slip ratio 5%)		0~1.7 (0~1.6) / Space between hills 26•30cm 0-1.3 (0-1.2)		
Planting efficiency (min./10a)		9 -		

○Seedling tray for 4 mats (one side) 7.3kg ○Seedling slider (one side) 24kg ○ seedling tray for 16 mats 65kg

※Sub seedling tray, seedling slider, Back mirrors to be available and sold separately.

There are some possibilities to change this specification without prior notice for improvement.