

■主要諸元表 GS182・GS202・GS232・GS252

名 称	GS182		GS202			GS232				GS252									
	J	M	J	M	MT	SJ	J	M	MT	LJ	J	M	MT	SJ	XJ	XM	XMT		
駆動方式	4輪駆動																		
機 体 寸 法	全 長 (mm)	2650					2710				2650	2790							
	全 幅 (mm)	1095			1145		1150			1165		1145		1270					
	全 高 (mm)	1900			1815		1925			1950		1815		1970					
	軸 距 (mm)	1380					1450				1380		1500						
	前輪トレッド (mm)	865			875		930				875		990						
	後輪トレッド (mm)	810,960			940		880,1030				940		1030						
	最低地上高 (mm)	335		265		360			375		265		375						
	質 量 (kg)	850		890		835		915		955		925		965		835		1150	
エ ン ジ ン	名 称	S3L					S3L2												
	種 類	水冷4サイクル3気筒ディーゼル																	
	総排気量 (L(cc))	1.125{1125}					1.318{1318}												
	出力/回転数 (kW(PS)/rpm)	13.2{18}/2500		14.7{20}/2500			16.9{23}/2500			18.4{25}/2500									
	燃烧室型式	渦流室																	
	使用燃料	ディーゼル軽油																	
	燃料タンク容量 (L)	23.0																	
バッテリー (V/Ah)	55B24R 12・36																		
走 行 部	前輪タイヤ	6.00-12-4PR			5.00-12.4PR		6-14-4PR		7-14-4PR		5.00-12.4PR		7-14-4PR						
	後輪タイヤ	8.3-22-4PR			8-16-4PR		9.5-22-4PR		9.5-24-4PR		8-16-4PR		9.5-24-4PR						
	クラッチ形式	乾式単板																	
	ブレーキ形式	湿式ディスク式																	
	ステアリング形式	パワーステアリング (全油圧式)																	
	変速方式	常時噛み合い式+選択摺動式 [EZドライブ(T仕様)：油圧無段変速併用]																	
	変速段数 (段)	前進12	後進12	前進30 後進15	前進12	後進12	前進30 後進15	前進12	後進12	前進30 後進15	前進12	後進12	前進30 後進15	前進12	後進12	前進30 後進15			
	走行速度 (km/h) []内は最高速度	前 進	0.24~13.10[14.10]		0~ 12.37 [13.31]	0.19~ 13.01 [14.00]	0.19~13.03 [14.02]	0~ 12.08 [13.00]	0.20~13.75[14.79]		0~ 12.75 [13.72]	0.19~ 13.01 [14.00]	0.20~13.75 [14.79]	0~ 12.75 [13.72]					
		後 進	0.22~12.04[12.96]		0~ 8.19 [8.81]	0.17~ 11.96 [12.86]	0.17~11.97 [12.88]	0~ 8.00 [8.61]	0.18~12.64[13.60]		0~ 8.44 [9.08]	0.17~ 11.96 [12.86]	0.18~12.64 [13.60]	0~ 8.44 [9.08]					
	最小旋回半径 (m)	1.9			1.8			2.0		1.9		2.1							
P T O	回転速度 (rpm)	正転566、816、1310 逆転952																	
	軸径 (mm)	35 (6スプライン)																	
操 縦 機 器	油圧制御	ポジションコントロール																	
	装着方式	3点リンク JIS O型																	
安全フレーム																			
安全キャブ																			
安全鑑定合格番号																			
運転免許	小型特殊自動車																		

※この諸元は改良のため予告なく変更する場合があります。

■型式区分及び装備一覧表

		GS182		GS202			GS232				GS252									
		J	M	J	M	MT	SJ	J	M	MT	LJ	J	M	MT	SJ	XJ	XM	XMT		
油 圧 リ フト	個 別 機 能	機械式耕深制御	●		●			●	●			●	●			●	●			
		JACマイコン式水平制御 (ジャイロ付き)	●		●			●	●			●	●			●	●			
		MACマイコン式耕深水平制御 (ジャイロ付き)		●		●	●			●	●			●	●			●	●	
		VRC制御		●		●	●			●	●			●	●			●	●	
		おまかせ機能		●		●	●			●	●			●	●			●	●	
		クイックアップ	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		旋回アップ	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		バックアップ	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Sモード		▲		▲	▲			▲	▲			▲	▲			▲	▲			
旋回補助 機能	倍速旋回	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	オートブレーキ旋回	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
EZドライブ (HST)						●								●						
リクライニングシート	●	●	●	●	●			●	●	●	●	●	●	●		●	●	●		
大型乗降アシストバー	●	●	●	●	●			●	●	●	●	●	●	●		●	●	●		
ハイマウントテールランプ	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
片ブレーキ誤操作防止装置	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
低速車マーク	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
灯火器スイッチ (オートリターン付)	●	●	●	●	●			●	●	●	●	●	●	●		●	●	●		
大型バックミラー	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲						
アクセサリ電源ソケット	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
小物入れ (スマートフォン置き)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
エンジンオイル切れ警報ランプ+ブザー	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
燃料供給台+満タンお知らせブザー	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
QRコードラベル	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
カップホルダ	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
シートベルトホルダ	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
キャビン	内外気切替エアコン															●	●	●		
	CDプレーヤー&FM/AMラジオ															●	●	●		
	作業灯 前2灯 後2灯															●	●	●		

J : JAC(マイコン式水平制御)仕様

M : MAC(マイコン式耕深水平制御)仕様

T : EZドライブ仕様 S : 低床仕様

L : 大型タイヤ仕様 X : キャビン仕様

▲ : 別売オプション